




Specifications Philips CoreLine RC132V LED Panel  
30x120cm 3000K 3400lm PSU OC | Warm White -  
Replaces 2x36W

[View Product](#)

General Information

|                          |                                  |
|--------------------------|----------------------------------|
| SKU                      | 234452                           |
| EAN                      | 8718699381035                    |
| Brand                    | Philips                          |
| Manufacturer Name        | RC132V LED34S/830 PSU W30L120 OC |
| Any Lamp all-in warranty | 5 Years                          |
| Average Lifetime (h)     | 50000                            |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 33              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 3400            |
| Luminous Efficacy (lm/W)    | 103             |

|                        |                                         |
|------------------------|-----------------------------------------|
| Suitable for Outdoor   | No                                      |
| IP-rating              | IP44                                    |
| Impact Protection (IK) | IK03 - 0.35 joule                       |
| Fixture Connection     | PIP [Push-in connector and pull relief] |
| Driver Included        | Yes                                     |
| Power factor           | >0.90                                   |
| Product Type Category  | LED Panel                               |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1200     |
| Width (mm)     | 300      |
| Height (mm)    | 32       |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy return process**